



MEGAMIX FREEZE A10



Applications

MEGAMIX FREEZE A10 quick-setting and quick-hardening agent (without chloride) can be used in all types of reinforced and non-reinforced mortars and concretes. With the use of this additive, due to the increase in the cement hydration rate, the process of obtaining the strength of concrete or mortar becomes faster, and as a result, it becomes possible to open the mold faster or apply the prestressing force earlier. At the same time, in cold weather, by using this additive, the duration of concrete processing and storage against freezing can be reduced.

Dosage

The consumption of MEGAMIX AIR E10 is recommended in the amount of 0.5 to 2% of the weight of cement materials. The amount of consumption is obtained according to the conditions of the place of implementation, the mixture design and laboratory tests.

Method of Use

MEGAMIX FREEZE A10 should be added to the mixture at the same time as water or after adding all the components. Make sure that this admixture is spread evenly throughout the mixture after mixing. Do not add this product directly to dry materials, especially cement.

How to maintain

Store in a covered place, temperature more than 5°C, and inside the package.

Under the correct storage conditions and in the original packaging, it can be consumed up to 24 months after production.

Packaging:

25 kg gallon / 250 kg barrel / 1200 kg tank

Technical support

We are ready to provide related technical services in the site.

Compatibility

If you need to use it simultaneously with other admixtures, be sure to contact the technical support department.

Standard

This product complies with ASTM C494: Type C and INSO 2930-2 (Tables 6 and 7) and EN 934-2 (Tables 6 and 7) standards.

Technical features

Product type: Liquid

Color: colorless to pale yellow

Specific mass (kg/L): 1.25 ± 0.03

pH: 13 ± 1